

Ci[™] Series Amplifiers



New to the Crest Audio family, the Ci[™] Series brings high-performance audio to the systems integration market. The Ci Series features an efficient, air-cooled power supply in a compact, 2RU chassis, with support for constant-voltage outputs for installations that require a wide variety of loads with efficient rack layouts. Support for optional monitoring and control make the Ci Series a perfect choice for applications where paging, fire-alarm or priority control is required. Additional support for NexSys® control modules extends the Ci Series into advanced systems where integrated control, audio transport and signal processing is required at the amplifier.

- Four- and eight-channel versions available
- Individual channels are selectable as low impedance or 70 volt
- Front- and rear-panel indicators for amplifier status
- Full amplifier control and monitoring via NexSys® 4 software or Peavey® MediaMatrix® product and digital audio distribution
- Variable-speed fan
- Sequential turn-on standard
- Euro-style input connectors
- Barrier strip output connectors
- One controlled-voltage input per channel standard
- One fault relay per channel standard
- 100- and 50-volt operation supported with external accessories
- EN60849 and ANSI160849 compliant with optional accessories
- TourClass® protection







Ci[™] Series Amplifiers

Ci amplifiers are designed to drive low-impedance or 70-volt speaker loads without bridging between channels, and can accommodate modules that facilitate load monitoring, digital audio delivery and Crest Audio's NexSys® networking.

		The Control of the Co	Total Canal
	Ci 20x8	Ci 30x4	
Dual Power			Chs Ch6 Ch7 Ch8
70V	200 W x 8	300 W x 4	_
8 Ω	200 W x 8	300 W x 4	
4 Ω	150 W x 8	200 W x 4	
Bridged Mono Power			
140V	400 W x 4	600 W x 2	
16 Ω	400 W x 4	600 W x 2	
8 Ω	300 W x 4	400 W x 2	
4 Ω			
Class	D	D	
Rack Space	2	2	
Weight	36.5 lbs. (16.65 kg)	34 lbs. (14.83 kg)	

